

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 1

Compilation date: 20/02/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ROAR 900 EXTREME CUT GELCOAT COMPOUND

Product code: 900-10

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC31: Polishes and wax blends.

1.3. Details of the supplier of the safety data sheet

Company name: Roar Advanced Finishing Ltd

Unit 2c Bradley Park High Holborn Road

Ripley
Derbyshire
DE5 3NW

United Kingdom

Tel: 01773 743492

Email: rob@roar-polishing.com

1.4. Emergency telephone number

Emergency tel: 01773 743492

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH066; -: EUH208

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Contains 1,2-

benzisothiazolin-3-one. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 2

3.2. Mixtures

Hazardous ingredients:

CALCINED ALUMINA - REACH registered number(s): 01-2119529248-35

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-691-6	691-6 1344-28-1 Substance with a Community		-	10-30%
		workplace exposure limit.		

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS - REACH registered number(s): 01-2119456810-40

920-901-0	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%
-----------	---	---	------------------------------	--------

HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-21194557735-29

919-029-3 -	-	Substance with a Community	Asp. Tox. 1: H304; -: EUH066	1-10%
		workplace exposure limit.		

ANHYDROUS ALUMINIUM SILICATE

296-473-8	92704-41-1	Substance with a Community	-	<1%
		workplace exposure limit.		

Non-classified ingredients:

HYDROCARBONS, C11-C14, N-ALKANKES, ISOALKANES, CYCLIS, <2% AROMATICS - REACH registered number (s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304	1-10%

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number (s): 01-21194557273-39

WHITE MINERAL OIL 2 - REACH registered number(s): 01-2119487078-27

232-455-8	8042-47-5	-	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 3

Delayed / immediate effects: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1200mg/m3	-	-	-

HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

UK 5 mg/m3	-	-	_
------------	---	---	---

ANHYDROUS ALUMINIUM SILICATE

UK	10 mg/m3	-	-	-
----	----------	---	---	---

DNEL/PNEC Values

Hazardous ingredients:

CALCINED ALUMINA

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	3 mg/m3	Workers	Local

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: White

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Kinematic viscosity: 35,000cps

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 5

Viscosity test method: Brookfield @20degC

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 65 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 1.10 pH: 7-9

VOC g/I: 108

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 6

Inhalation: No symptoms.Delayed / immediate effects: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C13, ISOALKANES, <2% AROMATICS

	= 0 - 0		_
Daphnia magna	48H EC50	1000	mg/l

HYDROCARBONS, C16-C20, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

FISH	96H LC50	1028	mg/l
MARINE ALGAE (Skeletonema costatum)	72H ErC50	3196	mg/l
MARINE ALGAE (Skeletonema costatum)	72H IC50	3198	mg/l

ANHYDROUS ALUMINIUM SILICATE

FISH	96H LC50	>1000	ma/l
1		,	·····9/·

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable.

Waste code number: 08 04 12

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

ROAR 900 EXTREME CUT GELCOAT COMPOUND

Page: 7

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H304: May be fatal if swallowed and enters airways.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.